

# Package: reinstallr (via r-universe)

November 5, 2024

**Type** Package

**Title** Search and Install Missing Packages

**Version** 0.1.4

**Author** Calli Gross

**Maintainer** Calli Gross <calli@calligross.de>

**Description** Search R files for not installed packages and run  
install.packages.

**License** GPL-3

**URL** <https://github.com/calligross/reinstallr/>

**LazyData** TRUE

**RoxygenNote** 7.1.2

**Suggests** testthat

**Depends** R (>= 3.3.0)

**Repository** <https://calligross.r-universe.dev>

**RemoteUrl** <https://github.com/calligross/reinstallr>

**RemoteRef** HEAD

**RemoteSha** a33e94e785f03ca3b69dec61da478f9edb2bb63d

## Contents

find_used_packages . . . . .	2
reinstallr . . . . .	2
show_missing_packages . . . . .	3
show_package_stats . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

find\_used\_packages      *Find Files Where Specific Packages Are Used*

---

### Description

Find Files Where Specific Packages Are Used

### Usage

```
find_used_packages(packages, path = NULL, pattern = NULL)
```

### Arguments

packages	Vector of packages to look for
path	Directory which is scanned recursively. Default is the working directory.
pattern	Regex to identify R source files. Default is <code>.*\\.(R Rnw Rhtml Rpres Rmd)\$</code>

### Value

A data.frame with the files which are using the specified packages

### Examples

```
## Not run:
find_used_packages('dplyr', path = '../')

## End(Not run)
```

---

reinstallr      *reinstallr*

---

### Description

reinstallr

### Usage

```
reinstallr(path = NULL, pattern = NULL, ...)
```

### Arguments

path	Directory which is scanned recursively. Default is the working directory.
pattern	Regex to identify R source files. Default is <code>.*\\.(R Rnw Rhtml Rpres Rmd)\$</code>
...	Parameters passed to <code>install.packages()</code>

**Details**

reinstallr() scans all R source files in the path specified by the path parameter and matching the pattern regex. reinstallr looks for library(package), require(package) and package::function

---

show\_missing\_packages *Show used but not installed packages*

---

**Description**

Show used but not installed packages

**Usage**

```
show_missing_packages(path = NULL, pattern = NULL, ...)
```

**Arguments**

path	Directory which is scanned recursively. Default is the working directory.
pattern	Regex to identify R source files. Default is <code>.*\.(R r Rnw Rhtml Rpres Rmd)\$</code>
...	Parameters passed to available.packages()

**Details**

show\_missing\_packages() searches missing packages and checks if they are available on CRAN

**Value**

A data.frame with missing packages

**Examples**

```
## Not run:  
show_missing_packages('../')  
  
## End(Not run)
```

---

show\_package\_stats     *Show Used Packages*

---

**Description**

Show Used Packages

**Usage**

```
show_package_stats(path = NULL, pattern = NULL)
```

**Arguments**

path             Directory which is scanned recursively. Default is the working directory.  
pattern          Regex to identify R source files. Default is `.*\.(R|r|Rnw|Rhtml|Rpres|Rmd)$`

**Value**

A aggregated data.frame

**Examples**

```
## Not run:  
show_package_stats('../')  
  
## End(Not run)
```

# Index

`find_used_packages`, [2](#)

`reinstallr`, [2](#)

`show_missing_packages`, [3](#)

`show_package_stats`, [4](#)